ST CLAIR -LAC 650 SL

UPF 50+ | 680 g/m² | M2 / B1 / BS NFPA701 B-S2-D0 | 3m

ST CLAIR White

7462

7458 (RAL 1015)

7409

7534

654

652

7419

810

941

7309

7500

7507

7456

995

ST CLAIR - LAC 650 SL

COLOR			Gtot EXT			
White	77	12	0,09		9-10	
7462	73	16	0,09		9	
7458	68	24	0,08		5	
7409	54	41	0,07		0,2	
7534	14	86	0,08		0	
654	46	54	0,05		0	
652	26	74	0,07		0	
7419	6	94	0,09		0	
810	5	95	0,09		0	
941	27	66	0,1		0	
7309	9	90	0,09		0	
7500	47	42	0,11		0,7	
7507	24	71	0,1		0,2	
7456	53	35	0,11		7	
995	22	72	0,06		0	

SUNBLOCK

COLOR			Gtot EXT			
7279	72	28	0,02		0	
7398	68	32	0,03		0	
654	45	55	0,05		0	
7543	72	28	0,02		0	
7464	68	32	0,03		0	
7545	45	55	0,05		0	
7463	72	28	0,02		0	
7469	45	55	0,05		0	
7510	16	84	0,08		0	
7511	68	32	0,03		0	
7512	45	55	0,05		0	
7481	72	28	0,02		0	
7482	68	32	0,03		0	

BLOCKLIGHT

COLOR			Gtot EXT			
7279	72	28	0,02		0	







Solar Reflexion (%)

Solar Absorption (%)

Gtot EXT — Solar factor of the combination of fabric + reference glazing C

Opaque

Thermal Comfort

Visual Transmission (%)

Visual Protection

UV Protection 100% (UPF 50+)

SUNBLOCK

UPF 50+ | 850 g/m² | M2 / B1 / BS NFPA701 B-S2-D0 | 3m

SUNBLOCK

7279

7398

654

SUNBLOCK HERRINGBONE

7543

7545

SUNBLOCK GRAIN

7463

7469

7464

SUNBLOCK MOSAIC

7510

7512

7511

SUNBLOCK 3D

7481

7482

BLOCKLIGHT

7279

UPF 50+

640 g/m²

M2

25% lighter
25% plus léger / 25% leichter
25% más ligero / 25% più leggero

Suppleness
Souplesse / Flexibilität
Flexibilidad / Buona flessibilità

3m

SYSTEM LOWICK

Dickson's unique anti-wicking process helps the fabric to last longer and look like new.

Classic coatings



Moisture penetration

Dickson's LOWICK System



Total coating impregnation of the yarn

FINITION CLEANGARD

The smooth Cleangard topcoat lacquer prevents soiling and facilitates cleaning. A solid protection against weathering.

ADVANTAGES

- All-weather resistant
- Easier to clean
- Very good weldability
- Longer life
- Suppleness
- Smoother surface, less prone to soiling.

Dickson PVC fabrics are recyclable

MADE IN FRANCE

REACH COMPLIANCE

vinyl plus COMMITTED TO SUSTAINABLE DEVELOPMENT

St Clair PVC Collection

Architectural PVC | A seriously smart outdoor fabric

Goodearl × Bailey

	Blocklight	Lac 650 SL	Sunblock
Base cloth	550 dtex PES HT	1100 dtex PES HT	1100 dtex PES HT
Width	3.00 m	3.00 m	3.00 m
Roll length	30 mtr	30 mtr	30 mtr
Coating	PVC (Lowick)	PVC (Lowick)	PVC (Lowick)
Finish	Cleangard	Cleangard	Cleangard
Total weight	640 g/m²	680 g/m²	850 g/m²
Tensile strength > NF EN ISO 1421	150/150 daN	260/250 daN	260/250 daN
Tear strength > DIN 53363	15/15 daN	32/28 daN	32/28 daN
Adhesion > NF EN ISO 2411	7 daN / 5 cm	8 daN / 5 cm	8 daN / 5 cm
Elongation under load (W / W) > NF EN 15619	<1% / <3%	<1% / <2%	<1% / <2%
Residual deformation (W / W) > NF EN 15619	<0.4% / <0.8%	<0.4% / <0.8%	<0.4% / <0.8%
Temperature resistance > NF EN 1876-2	-30°C +70°C	-30°C +70°C	-30°C +70°C
Flame Retardancy > NF P 92503 / DIN 4102 / BS 7837	M2	M2 / B1 / BS NFPA701 B-S2-D0	M2 / B1 / BS NFPA701 B-S2-D0

Average values, non-contractual
Valeurs moyennes, non-contractuelles / Alle angegebenen Werte sind ca.Werte / Valores medios y no contractuales / Questi valori medi non hanno valore contrattuale

IMPRIM'VERT 12/2015

Phone. 61 2 9316 1300
Email. sales@goodearlandbailey.com.au
goodearlandbailey.com.au

Goodearl × Bailey

DICKSON COATINGS

GLEN RAVEN

Glen RavenTM is a trademark and Dickson® is a registered trademark of Glen Raven, Inc.